



Black Diamond Track Parts Pvt. Ltd.

Established in the year 1991 as manufacturer of mining equipments, Black Diamond Track Parts Pvt. Ltd. manufactures & supplies mining material handling and general engineering equipment. This covers all aspects of designing, planning, production, installation and commissioning, maintenance support and even supply of critical spares.

Tip Trailer (26 Cum) Specifications

Description	Specifications
PAYLOAD CAPACITY	29/30 T
UNLADEN WEIGHT OF TRAILER	8.5 T
VOLUME	26 Cum.
OVERALL DIMENSION OF TRAILER	6.948 x 2.388 x 1.570 (L x W x H (m))
HYDRAULICS	HYVA FE-149-3 Stage/Equivalent
ANGLE OF TIP	41° Max
CHASSIS	FABRICATED 400 x 180 NPB (JINDAL)
STEEL GRADE	"BSK46 YS(Mpa) - 460-540 min., UTS(Mpa) - 500-620, EL 21%"
LANDING LEG	Two speed type front supports shall be provided at the front end. Make: York or Equivalent
AXLE	3 Nos. 13T/16T Axles @ 105 km/hr., Track-1940 mm. (88") (Make: YORK/FUWA OR EQUIVALENT)
BRAKE-TYPE	AIR (Twin line brake system coupled to tractor brake system)
KING PIN	O 50.8 mm kingpin York/Jost/FUWA/Equivalent
SUSPENSION	Tridem axle with load equalizing brackets.16 T capacity.
TYRES & WHEEL RIMS	10.00 X 20 - 16 PR - 12 Nos. 7.5 X 20 - 12 Nos.
WELDING	MIG/ARGOSHEILD COMBINATION
PAINTING & SHOT BLASTING	One coat of primer after Shot Blasting and Two coats of finish quick dry paint to color of customer choice.



Consult with our expert team

www.bdtp.in | contact@bdtp.in

+91 9229 297 009 | +91 7879 027 991

Black Diamond Track Parts Pvt. Ltd.

Plot No. 20, Sector - C, Sirgitti Industrial Area, Bilaspur, Chhattisgarh - 495004, India.

Ancillary to SECL An ISO 9001:2000 Company SSI Reg No: 100512316

Tip Trailer (34 Cum) Specifications

Description	Specifications
PAYLOAD CAPACITY	37 T
UNLADEN WEIGHT OF TRAILER	9.5 T
VOLUME	34 Cum.
OVERALL DIMENSION OF TRAILER	8.063 x 2.388 x 1.770 (L x W x H (m))
HYDRAULICS	HYVA FE-169-4 Stage/Equivalent
ANGLE OF TIP	45° Max
CHASSIS	FABRICATED 450 x 180 NPB (JINDAL)
STEEL GRADE	"BSK46 YS(Mpa) - 460-540 min., UTS(Mpa) - 500-620, EL 21%"
LANDING LEG	Two speed type front supports shall be provided at the front end. Make: York or Equivalent
AXLE	3 Nos. 13T/16T Axles @ 105 km/hr., Track-1940 mm. (88") (Make: YORK/FUWA OR EQUIVALENT)
BRAKE-TYPE	AIR (Twin line brake system coupled to tractor brake system)
KING PIN	0 50.8 mm kingpin York/Jost/FUWA/Equivalent
SUSPENSION	Tridem axle with load equalizing brackets.16 T capacity.
TYRES & WHEEL RIMS	10.00 X 20 - 16 PR - 12 Nos. 7.5 X 20 - 12 Nos.
WELDING	MIG/ARGOSHEILD COMBINATION
PAINTING & SHOT BLASTING	One coat of primer after Shot Blasting and Two coats of finish quick dry paint to color of customer choice.



Consult with our expert team

www.bdtp.in | contact@bdtp.in

+91 9229 297 009 | +91 7879 027 991

Black Diamond Track Parts Pvt. Ltd.

Plot No. 20, Sector - C, Sirgitti Industrial Area, Bilaspur, Chhattisgarh - 495004, India.

Ancillary to SECL An ISO 9001:2000 Company SSI Reg No: 100512316